

(TYPE 01)

TEMPERATURE & HUMIDITY SENSOR SPECIFICATIONS

Sensor & Gateway -

Features

- Long Range Industrial Wireless IoT Remote Temperature Humidity Sensor
- 2 Mile Line-of-Sight Range with On-Board Antenna
- Superior LOS Range of up to 28 Miles with High-Gain Antennas
- Configurable Sleep duration

Sensor Environmental and Regulatory Qualifications

- Humidity Range 0-90%
- Wall-Mounted or Magnet Mounted
- IP65 Rated Enclosure
- Flammability Rating of UL94 HB
- RoHS Compliant

Sensor Data

- Industrial Grade with a Sensor Resolution of ±2%RH ±0.2°C
- Sensor Probe Operating Temperature Range: -40°C to +125°C
- Sensor Probe Operating Humidity Rating up to 90% Humidity
- CPU/Wireless module housing (box) Operating Temperature Range:
 -40°C to +85°C
- Batteries 4 AA (L91)



Specifications

- Sensor: 4.5"L x 3.25"W x 2.5"H
- Sensor Weighs .78 lb
- Gateway: 11.5"H (with antennae) x 4.1"W x 4.25"D
- Gateway Weighs 3 lbs

APPLICATIONS



In-House Temperature Humidity Monitoring



Factory Floor Temperature Monitoring



Storage Unit Weather Monitoring System



Warehouse Temperature Humidity Monitoring System

Software -

Dashboard

- Easy to Understand Telemetry Graphs for Temperature and Humidity
- Sensor Battery Level
- Toggle Between Celsius and Fahrenheit
- Easy to Recognize Notification Features Designed to Reduce Alert Fatigue

Customization

- Easily Map Your Equipment With Your Terminology
- · Create Unique Comparisons to Track Like Equipment